

Model GC100S Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Stdby Power 110kVA / 88 kW Prime Output 100kVA / 80 kW Noise Level @ 7m 72 dB(A) Fuel Capacity 540 Litres Length 3.14m Width 1.21m Height 1.80m Weight 2114 kg

Engine

Manufacturer Cummins Diesel
Engine Model 6BT5.9G1
Type & Cylinder 4 Stroke – 4 L
Induction Turbocharged
Fuel Consumption
22L @ 100%, 17L @ 75%, 11L @ 50% Load
Coolant Capacity 10.5 L
Governor Mechanical
Cubic Capacity 5.9 L
Oil Capacity 16 L

Alternator

Alternator Brand / Model Stamford / UCi274C
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Controls

Controller DeepSea 7420 with LCD Metering Circuit Breaker Four Pole Battery Isolator Fitted adjacent battery

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points

Canopy Centre Lift, lockable doors with control panel viewing window

Path Finish Heavy duty powder coat finish white canopy with a black base

Emergency Stop External Emergency Stop

Options

Outlets Single or 3 Phase Options PMG OPTION