



Genette



GC130S

Model GC130S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 143kVA / 116 kW
Prime Output 130kVA / 104 kW
Noise Level 72 dB(A)
Fuel Capacity 620 Litres

Length 3.31m
Width 1.19m
Height 1.97m
Weight 2257 kg

Engine

Manufacturer Cummins Diesel
Engine Model 6BTA5.9G2
Type & Cylinder 4 Stroke – V16
Induction Turbocharged Air to Air After Cooled
Fuel Consumption
30 L @ 100%, 23L @ 75%, 16L @ 50% Load
Coolant Capacity 10.4 L
Governor Electronic
Cubic Capacity 5.9 L
Oil Capacity 16.4 L

Options

Outlets Single or 3 Phase Options
PMG Option

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / UCi274E
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted