



Genette



GC1500S

Model GC1500S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 1650kVA / 1320 kW
Prime Output 1500kVA / 1200 kW
Noise Level 87dB(A) @ 7m
Fuel Capacity 900 Litres

Length 6.05m
Width 2.43m
Height 2.59m
Weight 16,840 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA50GS8
Type & Cylinder 4 Stroke – V16
Induction Turbocharged After Cooled
Fuel Consumption
309 L @ 100%, 238 L @ 75%, 167 L @ 50% Load
Coolant Capacity 351 L
Governor Electronic
Cubic Capacity 50 L
Oil Capacity 204 L

Options

Synchronizing
Grid / Mains, Max Demand Lopping, Multiple sets
Protection RCD/ELCB IP30 or IP66
PMG MX321

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Three Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / Pi734C
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Container Set

40' Container
ISO Container HC, with integral muffler
Paint Finish
Heavy duty powder coat finish White
Emergency Stop External Emergency Stop Fitted