



Genette

GC30S

Model GC30S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 33kVA / 26 kW
Prime Output 30kVA / 24 kW
Noise Level @ 7m 67 dB(A)
Fuel Capacity 270 Litres

Length 2.588m
Width 1.1m
Height 1.707m
Weight 1408 kg Dry

Engine

Manufacturer Cummins Diesel
Engine Model 4B3.9G1
Type & Cylinder 4 Stroke – 6 L
Induction Naturally Aspirated
Fuel Consumption
6.7L @ 100%, 5.2L @ 75%, 4.0L @ 50% Load
Coolant Capacity 8 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 11 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Included
Battery Charger 24vDC 5amp

Alternator

Alternator Brand / Model Stamford / Pi144G
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Outlets Single or 3 Phase Options
PMG EBS option

