

Model GC312S Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Stdby Power 345kVA / 276 kW Prime Output 312kVA / 250 kW Noise Level @ 7m 75 dB(A) Fuel Capacity 1650 Litres Length 4.25m Width 1.42m Height 2.42m Weight 4772 kg

Engine

Manufacturer Cummins Diesel
Engine Model NTA855G1B
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
69 L @ 100%, 51 L @ 75%, 35 L @ 50% Load
Coolant Capacity 61 L
Governor Electronic
Cubic Capacity 14 L
Oil Capacity 38.6 L

Options

Outlets Single or 3 Phase Options **PMG** Option

Controls

Controller DeepSea 7420 with LCD Metering Circuit Breaker Four Pole Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / HCi444ES
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points

Canopy Centre Lift, lockable doors with control panel viewing window

Path Finish Heavy duty powder coat finish white canopy with a black base

Emergency Stop External Emergency Stop