



Genette



GC375S

Model GC375
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 390kVA / 296 kW
Prime Output 375kVA / 300 kW
Noise Level @ 7m 76 dB(A)
Fuel Capacity 1600 Litres

Length 4.42m
Width 1.51m
Height 2.57m
Weight 4908 kg

Engine

Manufacturer Cummins Diesel
Engine Model NTAA855G7
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
83.8 L @ 100%, 62 L @ 75%, 42 L @ 50% Load
Coolant Capacity 61 L
Governor Electronic
Cubic Capacity 14 L
Oil Capacity 38.6 L

Options

Outlets Single or 3 Phase Options
PMG Option

Controls

Controller DeepSea DSE7420 with LCD Metering
Circuit Breaker Four Pole MCB
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / HCi444FS
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bundled fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop