



Genette

GC40S

Model GC40S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Study Power 44kVA / 35.2kW
Prime Output 40 kVA / 32kW
Noise Level @ 7m 67dB(A)
Fuel Capacity 270 Litres

Length 2.58m
Width 1.08m
Height 1.7m
Weight 1388 kg

Engine

Manufacturer Cummins Diesel
Engine Model 4BT3.9G1
Type & Cylinder 4 Stroke – 4 L
Induction Turbocharged
Fuel Consumption
9.4L @ 100%, 6.2L @ 75%, 4.5L @ 50% Load
Coolant Capacity 8 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 11 L

Options

Outlets Single or 3 Phase Options
PMG EBS Option

Controls

Controller DeepSea 7420 with Analog Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / Pi144K
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912