GC575S

Model GC575S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 640kVA / 512 kW
Prime Output 575kVA / 460 kW
noise Level (dBA @ 7m) 77dB(A)
Fuel Capacity 945 Litres

Length 4.79m
Width 1.95m
Height 2.66m
Weight 7392 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA19G6
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
127 L @ 100%, 95 L @ 75%, 64 L @ 50% Load
Coolant Capacity 91 L
Governor Electronic
Cubic Capacity 15 L
Oil Capacity 50 L

Options

Synchronizing
Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG MX341 or MX321

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole
Emergency Stop Included

Alternator

Alternator Brand / Model Stamford / HCi544E
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
6 Flindell Street, O'Connor WA 6163

CALL US
1300 305 912