



GC800S

Model GC800S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 825kVA / 660 kW
Prime Output 800kVA / 640 kW
Noise Level @7m 87dBA(A)
Fuel Capacity 1150 L

Length 6.058m
Width 2.44m
Height 2.73m
Weight 12,100 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA38G2B
Type & Cylinder 4 Stroke – V12
Induction Turbocharged After Cooled
Fuel Consumption
172 L @ 100%, 135 L @ 75%, 94 L @ 50% Load
Coolant Capacity 98 L
Governor Electronic
Cubic Capacity 38 L
Oil Capacity 103 L

Options

Synchronizing
Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG MX341 or MX321

Controls

Controller DeepSea DSE7420 with LCD Metering
Circuit Breaker Four Pole
Emergency Stop Included

Alternator

Alternator Brand / Model Stamford / LV634C
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Container Set

20' Container
ISO Container HC, with integral muffler
Paint Finish
Heavy duty powder coat finish White
Emergency Stop
External Emergency Stop Fitted

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912