



Genette

GK30S

Model GK30S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power kVA / kW 33kVA / 26kW
Prime Output kVA / kW 30 kVA / 24kW
Noise Level (dBA @ 7m) 71dBA(A)
Fuel Capacity 180 Litres

Length 2.3m
Width 1.15m
Height 1.55m
Weight 1276 kg

Engine

Manufacturer Kubota Diesel
Engine Model V3300-BG
Type & Cylinder 4 Stroke – 4 L
Induction Naturally Aspirated
Fuel Consumption
7.7L @ 100%, 5.9L @ 75%, 4.2L @ 50% Load
Coolant Capacity 8.2 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 13.2 L

Outlets

Outlets 3 Phase
1 x Three phase, 3 x Single phase
Protection RCD/ELCB IP66
EBS PMG Option MX341 or MX321

Controls

Controller Remote Start with LCD Display
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford UCi224D
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted