



# Genette

## GP1000S

**Model** GP1000S  
**Speed** 1500 RPM  
**Phase/Voltage** 3, 415  
**Frequency** 50 Hz

**Standby Power** 1100kVA / 880 kW  
**Prime Output** 1000kVA / 800 kW  
**Noise Level (dBA @ 7m)** 87dB(A)  
**Fuel Capacity** 1150 Litres

**Length** 6.06 m  
**Width** 2.44 m  
**Height** 2.73 m  
**Weight** 11,570 kg

### Engine

**Manufacturer** Perkins Diesel  
**Engine Model** 4008-TAG2A  
**Type & Cylinder** 4 Stroke – 6 L  
**Induction** Turbocharged After Cooled  
**Fuel Consumption** 194 L @ 100%,  
142 L @ 75% Load, 97 L @ 50%  
**Coolant Capacity** 105 L  
**Governor** Electronic  
**Cubic Capacity** 22.9 L  
**Oil Capacity** 123L

### Controls

**Controller** DeepSea 7420 with LCD Metering  
**Circuit Breaker** Four Pole  
**Battery Isolator** Fitted adjacent battery

### Canopy

**20' Container** ISO Container HC, with integral muffler  
**Paint Finish** Heavy duty powder coat finish White  
**Emergency Stop** External Emergency Stop Fitted

### Options

**Synchronizing** Grid / Mains, Max Demand Lopping  
**Protection** RCD/ELCB IP30 or IP66  
**PMG** R450 &/or AREP

### Alternator

**Alternator Brand / Model** Leroy Somers LSA50.2S3  
**Type** Brushless  
**Harmonic Distortion** Less than 5%  
**Protection Class** IP 23  
**Insulation Class** Class H

East Coast Head Office Ph. 1300 305 912  
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627  
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912  
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219  
2/6 Quantum Link, Wangara WA 6065

**CALL US**  
**1300 305 912**