



Genette

GP1250

Model GP1250
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 1375kVA / 1100 kW
Prime Output 1250kVA / 1000 kW
Fuel Capacity Nil

Length 4.8 m
Width 1.83 m
Height 2.36 m
Weight 8859 kg

Engine

Manufacturer Perkins Diesel
Engine Model 4012-46TWG2A
Type & Cylinder 4 Stroke – V12
Induction Turbocharged After Cooled
Fuel Consumption 258 L @ 100%,
196 L @ 75%
Coolant Capacity 155 L
Governor Electronic
Cubic Capacity 45.8 L
Oil Capacity 203 L

Controls

Controller Remote Start with LCD Metering
Circuit Breaker Four Pole
Battery Isolator

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG R450

Alternator

Alternator Brand / Model Leroy Somers LSA50.2M6
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912