



Genette

GP1500S

Model GP1500S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 1650kVA / 1320 kW
Prime Output 1500kVA / 1200 kW
Noise Level (dBA @ 7m) 77dB(A)
Fuel Capacity 2000 Litres

Length 12.19 m
Width 2.44 m
Height 3.16 m
Weight 20,220 kg

Engine

Manufacturer Perkins Diesel
Engine Model 4012-46TAG2A
Type & Cylinder 4 Stroke – V12
Induction Turbocharged After Cooled
Fuel Consumption 300 L @ 100%,
230 L @ 75%, 160 @ 50% Load
Coolant Capacity 201 L
Governor Electronic
Cubic Capacity 45.8 L
Oil Capacity 177 L

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Canopy

20' Container ISO Container HC, with integral muffler
Paint Finish Heavy duty powder coat finish White
Emergency Stop External Emergency Stop Fitted

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG R450 &/or AREP

Alternator

Alternator Brand / Model Leroy Somers LSA50.2L8
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912