



Genette

GP150S

Model GP150S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 165kVA / 132 kW
Prime Output 150kVA / 120 kW
Noise Level (dBA @ 7m) 73dB (A)
Fuel Capacity 1087 Litres

Length 3.51 m
Width 1.22 m
Height 2.15 m
Weight 2259 kg

Engine

Manufacturer Perkins Diesel
Engine Model 1106A-70TAG2
Type & Cylinder 4 Stroke – 6 L
Induction Turbo Charged After Cooled
Fuel Consumption 41 L @ 100%,
31 L @ 75% Load, 20 L @ 50% Load
Coolant Capacity 37.2 L
Governor Electronic
Cubic Capacity 5.99 L
Oil Capacity 19 L

Alternator

Alternator Brand / Model Leroy Somers
LSA44.3L10
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Paint Finish Heavy duty powder coat finish white canopy with black base
Emergency Stop External Emergency Stop

Options

Outlets Single or 3 Phase Options
PMG R438

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912