



Genette

GP1750

Model GP1750
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 1925kVA / 1540 kW
Prime Output 1750kVA / 1400 kW
Fuel Capacity Nil

Length 5.7 m
Width 2.192 m
Height 3.44 m
Weight 15,700 kg

Engine

Manufacturer Perkins Diesel
Engine Model 4016TAG
Type & Cylinder 4 Stroke – V16
Induction Turbocharged After Cooled
Fuel Consumption 362 L @ 100%,
272 L @ 75%, 185 @ 50% Load
Coolant Capacity 255 L
Governor Electronic
Cubic Capacity 61.1 L
Oil Capacity 214 L

Controls

Controller Remote Start with LCD Metering
Circuit Breaker Four Pole
Battery Isolator

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG R450

Alternator

Alternator Brand / Model Leroy Somers LSA51.2S55
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912