



Genette

GP2000

Model GP2000
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 2200kVA / 1760 kW
Prime Output 2000kVA / 1600 kW
Fuel Capacity Nil

Length 6.28 m
Width 2.16 m
Height 2.57 m
Weight 13,198 kg

Engine

Manufacturer Perkins Diesel
Engine Model 4016TAG2A
Type & Cylinder 4 Stroke – V16
Induction Turbocharged After Cooled
Fuel Consumption 434 L @ 100%,
316 L @ 75%, 210 @ 50% Load
Coolant Capacity 316 L
Governor Electronic
Cubic Capacity 61.1 L
Oil Capacity 214 L

Controls

Controller Remote Start with LCD Metering
Circuit Breaker Four Pole
Battery Isolator

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG R450

Alternator

Alternator Brand / Model Leroy Somers LSA51.2M60
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912