



Genette

GP30S

Model GP30S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 33kVA / 26.4kW
Prime Output 30kVA / 24 kW
Noise Level (dBA @ 7m) 68dB (A)
Fuel Capacity 360 Litres

Length 2.34 m
Width 1.1 m
Height 1.71 m
Weight 1350 kg dry

Engine

Manufacturer Perkins Diesel
Engine Model 1103A-33G
Type & Cylinder 4 Stroke – 3 L
Induction Naturally Aspirated
Fuel Consumption 7.1L @ 100%,
5.4 L @ 75% , 3.9 L @ 50% Load
Coolant Capacity 10.2 L
Governor Mechanical
Cubic Capacity 3.3 L
Oil Capacity 8.3 L

Alternator

Alternator Brand / Model Leroy Somers
LSA43.2S25
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Controls

Controller Remote Start with LCD Metering
Circuit Breaker Two Pole
Battery Isolator Fitted adjacent battery

Options

Outlets 3 Phase N/A
Outlets Single Phase Option
PMG Option

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Paint Finish Heavy duty powder coat finish white canopy with black base
Emergency Stop External Emergency Stop

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912