



Genette

GP800

Model GP800
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 900kVA / 720 kW
Prime Output 800kVA / 640 kW

Length 3.8m
Width 1.71 m
Height 2.26 m
Weight 6415 kg

Engine

Manufacturer Perkins Diesel
Engine Model 4006-23TAG3A
Type & Cylinder 4 Stroke – 6L
Induction Turbocharged After Cooled
Fuel Consumption 164 L @ 100%,
124 L @ 75%, 86L @ 50% Load
Coolant Capacity 105 L
Governor Electronic
Cubic Capacity 22.9 L
Oil Capacity 123 L

Controls

Controller Remote Start with LCD Metering
Circuit Breaker Four Pole
Battery Isolator

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG R450

Alternator

Alternator Brand / Model Leroy Somers LSA49.1M75
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912