



Genelite



PLGCM250S

Model PLGCM250S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 275kVA / 220 kW
Prime Output 250kVA / 200 kW
Noise Level @ 7m 74 dB(A)
Fuel Capacity 1270 Litres

Length 3.66m
Width 1.212m
Height 2.253m
Weight 3105 kg

Engine

Manufacturer Cummins Diesel
Engine Model 6LTAA8.9G2
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged Air To Air After Cooled
Fuel Consumption
53 L @ 100%, 39L @ 75%, 27L @ 50% Load
Coolant Capacity 18 L
Governor Electronic
Cubic Capacity 8.9 L
Oil Capacity 27 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre lift, lockable doors with control panel viewing window
Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop fitted

Controls

Controller DeepSea 7320 with LCD Metering
Circuit Breaker 3 Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECO38-1LN
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG MX341 or MX321
Mine spec
Outlets
Jacket water heater

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912