



Genette



PLGCM350S

Model PLG350S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 375kVA / 300 kW
Prime Output 350kVA / 280 kW
Fuel Capacity 1700 Litres

Length 4.30m
Width 1.412m
Height 2.353m
Weight 4585 kg

Engine

Manufacturer Cummins Diesel
Engine Model NTA855G2A
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
76 L @ 100%, 59 L @ 75%, 39 L @ 50% Load
Coolant Capacity 61 L
Governor Electronic
Cubic Capacity 14 L
Oil Capacity 38.6 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre lift, lockable doors with control panel viewing window
Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop fitted

Controls

Controller DeepSea 7320 with LCD Metering
Circuit Breaker 3 Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte DCO383L4A
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Outlets Single or 3 Phase options
PMG option
Mine spec
Outlets
Jacket water heater

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912