



Genette



PLGCM500S

Model PLGCM500S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 550kVA / 440kW
Prime Output 500kVA / 400 kW
Noise Level (dBA @ 7m) 76dB(A)
Fuel Capacity 2600 Litres

Length 4.60m
Width 1.70m
Height 2.60m
Weight 5900 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA19G4
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
107 L @ 100%, 82 L @ 75%, 57 L @ 50% Load
Coolant Capacity 91 L
Governor Electronic
Cubic Capacity 19 L
Oil Capacity 50 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre lift, lockable doors with control panel viewing window
Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop fitted

Controls

Controller DeepSea DSE7320 with LCD Metering
Circuit Breaker 3 Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECO403S4A
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Synchronizing
Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG MX341 or MX321
Mine spec
Outlets
Jacket water heater

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912