

Model OZGPC140S Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Power Factor .8 Prime Output 140kVA / 112kW Standby Power 154kVA / 123kW Noise Level (dBA @ 7 m) 71.5dB(A) Fuel Tank Capacity 750 Litres Length 3.0m Width 1.106m Height 1.874m Weight 2100kg

Engine

Manufacturer Cummins Diesel

Engine Model 6BTAA5.9G2

Type & Cylinder 4 Stroke - 6 L

Induction Turbocharged Air to Air After Cooled

Fuel Consumption 30 L @ 100%

23 L @ 75%, 16 L @ 50% Load

Coolant Capacity 10.4 L

Governor Electronic

Cubic Capacity 5.9 L

Oil Capacity 16.4 L

Warranty World Wide as per 3381307 Publication

Alternator

Alternator Brand / Model OEM AVR Controlled

Type AC Brushless

Harmonic Distortion Less than 3%

Protection Class IP 23

Insulation Class Class H

Controls

Controller SmartGen HGM410 with LCD Display

Circuit Breaker Moulded Case 3 Pole

Battery Isolator Fitted with canopy adjacent battery

Canopy

Skid Base fuel tank with fork lift pockets and skid tie down points

Canopy Centre Lift, lockable doors with control panel viewing window

Paint Finish Heavy duty powder coat finish white canopy with a black base

Emergency Stop External Emergency Stop Fitted

Options

Outlets 1 x 32 AMP 3 Phase / 2 x 15 AMP Single Phase Weatherproof IP66

