

Model OZGPC160S Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Power Factor .8 Stdby Power 176kVA / 140kW Prime Output 160kVA / 128kW Noise Level (dBA @ 7 m) 71.5dB(A) Fuel Run Time 24 Hours Length 3.5 m Width 1.08 m Height 2.12 m Weight 2150 kg

Engine

Manufacturer Cummins Diesel

Engine Model 6CTA8.3G2

Type & Cylinder 4 Stroke - 6 L

Induction Turbocharged Air to Air After Cooled

Fuel Consumption 40 L @ 100%

30 L @ 75%, 20 L @ 50% Load

Coolant Capacity 13 L

Governor Electronic

Cubic Capacity 8.3 L

Oil Capacity 23 L

Warranty World Wide as per 3381307 Publication

Alternator

Alternator Brand / Model OEM AVR Controlled

Type AC Brushless

Harmonic Distortion Less than 3%

Protection Class IP 23

Insulation Class Class H

Controls

Controller SmartGen 6120 with LCD Display

Circuit Breaker Moulded Case 3 Pole

Battery Isolator Fitted with canopy adjacent

battery

Canopy

Skid Base fuel tank with fork lift pockets and skid tie down points

Canopy Centre Lift, lockable doors with control panel viewing window

Paint Finish Heavy duty powder coat finish white canopy with a black base

Emergency Stop External Emergency Stop Fitted

Options

Outlets 1 x 32 AMP 3 Phase / 2 x 15 AMP Single Phase Weatherproof IP66

