



# Genette



## GKM20S-1

**Model** GKM20S-1  
**Type** Medium Duty  
**Speed** 1500 RPM  
**Phase/Voltage** 1, 240  
**Frequency** 50 Hz

**Stdby Power** 22kVA / 18kW  
**Prime Output** 20kVA / 16kW  
**Noise Level (dBA @ 7m)** 61 dBA  
**Fuel Capacity** 37 Litres

**Length** 1.9m  
**Width** 0.75m  
**Height** 1.084m  
**Weight** 781 kg

### Engine

**Manufacturer** Kubota Diesel  
**Engine Model** V2203-BG  
**Type & Cylinder** 4 Stroke – 4 L  
**Induction** Naturally Aspirated  
**Fuel Consumption**  
5.0L @ 100%, 3.8L @ 75%  
**Coolant Capacity** 8.2 L  
**Governor** Mechanical  
**Cubic Capacity** 3.9 L  
**Oil Capacity** 8.7 L

### Outlets

**Outlets** Single Phase  
3 x 15amp IP66 with RCD MCBO  
**EBS PMG** Option

### Controls

**Controller** Remote Start with Analog Metering  
**Circuit Breaker** Two Pole  
**Battery Isolator** Fitted adjacent battery

### Alternator

**Alternator Brand / Model** Mecc Alte ECP32-2S/4  
**Type** Brushless  
**Harmonic Distortion** Less than 5%  
**Protection Class** IP 23  
**Insulation Class** Class H

### Canopy

**Canopy** Centre Lift, lockable doors with control panel viewing window  
**Path Finish** Heavy duty powder coat finish white canopy with a black base  
**Emergency Stop** External Emergency Stop Fitted

