



Genette



GKM30S-1

Model GKM30S-1
Type Medium Duty
Speed 1500 RPM
Phase/Voltage 1, 240
Frequency 50 Hz

Stdby Power 33kVA / 26kW
Prime Output 30kVA / 24kW
Noise Level (dBA @ 7m) 61 dBA
Fuel Capacity 70 Litres

Length 1.85m
Width 0.82m
Height 1.020m
Weight 840 kg

Engine

Manufacturer Kubota Diesel
Engine Model V3300-BG
Type & Cylinder 4 Stroke – 4 L
Induction Naturally Aspirated
Fuel Consumption
7.7 L @ 100%, 5.9 L @ 75%, 4.2 L @ 50% Load
Coolant Capacity 8.2 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 13.2 L

Options

Outlets Single Phase
3 x single phase
Protection RCD/ELCB IP66
EBS PMG MX341 or MX321

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Two Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP32-1L/4
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted

