




PORTABLE POWER MINE SPEC

KOHLER Diesel



Technical

Model	GKD5600E – Mine Spec
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	5.6kW
Continuous Output	7.0kVA
Noise Level (dBA @ 7m)	80
Frame	Extra Large Roll Frame

Engine

Manufacturer	Kohler
Engine Model	KD440E/10.2
Type	O.H.V.
Starting	Recoil & Electric Start
Fuel	Diesel
Run Time	2.3 hrs @ 100%, 3.2 hrs @75%
Tank Capacity	5.0 L
HP 3000 rpm cont	10.0 HP
Cubic Capacity	442 cm ³
Oil Capacity	1.5 L

Alternator

Alternator Brand	Mecc Alte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Controls

Key Start	Engine protection oil pressure
Emergency Stop	Fitted

Mine Spec Inclusions

Lockable Isolators	Battery, Starter & Control Panel
RCD 30ma	Fitted to Outlets
Fire Extinguisher	1kg
Jump Start	Anderson Plug
Bunded Tray	Included
Centre Lift	Included
Earth Stake	Included
Outlets	10amp or 15amp IP66 C/B RCD

Dimensions & Weight

Length	85cm
Width	55cm
Height	60cm
Weight	96kg

Options

Wheel Kits	Two Wheel or Four Wheel
BMA Certification	Optional