

INDUSTRIAL DIESEL UTILITY AIR **COMPRESSOR**



Technical

Model **CPS T175**

Type Box-Type Skid-Mounted Utility

Air Delivery 175CFM

Normal Effective 7bar(g) @ 100psi(g) **Working Pressure**

Engine

Manufacturer Kubota V 1505 T Type Starting Electric Start **Fuel** Diesel **Full Load RPM** 3000 RPM **Tank Capacity** 62 L Output Rating (kW/m) 32.5

Compressor

Single Stage Oil Injected Rotary Screw Air **Type**

Compressor

Lube Oil Capacity 5.5 L

Controls

Control Panel Key Start with Engine Protection

Blow Off Valve Automatic on Shutdown

Box Unit Dimensions & Weight

Length 1870mm Width 950mm Heiaht 1040mm Weight 704kg

Canopy

Canopy Galvanised Steel Canopy

Noise Level 70dB(A) @ 7m Spillage free frame Frame

Standard Features

Canopy Fully Silenced

Integrated lifting slots and top hook as standard

Fitted as Factory Standard **Aftercooler** Mounting Suitable for truck or trailer mounting

Fuel Autonomy Enough to run a full shift

Weight Under 750kg

Footprint At least 10% more compact than other models Maintenance Easy to service & long service intervals

Other Features

Mounting Suitable for truck mounting

Quality air options, water separator and multiple **Options**

points of customisation available



Authorized Distributor