CPS T SERIES UTILITY COMPRESSORS



FEN



## Technical

Engine

Model Туре Air Delivery **Normal Effective Working Pressure**  **CPS T110** Box-Type Skid-Mounted Utility 100CFM 7bar(g) @ 100psi(g)

**CPS T110** 

Manufacturer Type Starting Fuel **Full Load RPM Tank Capacity** Output Rating (kW/m)

Kubota D902 Electric Start Diesel 3600 RPM 30 L 18.5

### Compressor

Туре

Lube Oil Capacity

Single Stage Oil Injected Rotary Screw Air Compressor 3 L

#### Controls

**Control Panel Blow Off Valve** 

Key Start with Engine Protection Automatic on Shutdown

# **Box Unit Dimensions & Weight**

Length Width Height Weight 1580mm 740mm 850mm 488ka

### Canopy

Canopy Noise Level Frame

Galvanised Steel Canopy 70dB(A) @ 7m Spillage free frame

Fully Silenced

### **Standard Features**

Canopy

|               | - ,   |
|---------------|---|
|               | Integrated lifting slots and top hook as standard |
| Aftercooler   | Fitted as Factory Standard                        |
| Mounting      | Suitable for truck or trailer mounting            |
| Fuel Autonomy | Enough to run a full shift                        |
| Weight        | Under 750kg                                       |
| Footprint     | At least 10% more compact than other models       |
| Maintenance   | Easy to service & long service intervals          |
|               | · -   |
|               |   |

| Other Features |   |
|----------------|---|
| Mounting       | Suitable for truck mounting   |
| Options        | Quality air options, water separator and multiple points of customisation available |



**Authorized Distributor** 

The information given in this brochure is given for the benefit of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.