



C13 HIGH AMBIENT ENCLOSURES

50 Hz/60 Hz

These high ambient, factory installed enclosures incorporate internally mounted residential level silencers, designed for safety and aesthetic value on integral fuel tank base or optional dual wall integral fuel tank base for total fluid containment. These enclosures are of extremely rugged construction to withstand exposure to the elements and provide weather protection.

Picture shown may not represent actual package

Features

ROBUST/HIGHLY CORROSION RESISTANT CONSTRUCTION

- Factory installed on integral fuel tank base
- Environmentally friendly, polyester powder baked paint
- 1.6mm (0.063in) galvanized steel
- All round overhanging base to protect enclosure
- High-grade engineering thermoplastic corner posts for protection
- Integral lifting frame
- Compression door latches giving solid door seal
- Zinc plated or black coated stainless steel fasteners
- Internally mounted super critical exhaust silencing system

EXCELLENT ACCESS

- Large cable entry area for installation ease
- Accommodates rear mounted breaker and control panel
- Double doors on both sides
- Vertically hinged doors with solid bar door stays to hold doors open at 135° rotation
- Lube oil and coolant drains pipes to exterior of enclosure and terminated drain valves
- Radiator fill cover

SECURITY AND SAFETY

- Lockable access doors which give full access to control panel and breaker
- Cooling fan and battery charging alternator fully guarded
- Fuel fill, oil fill and battery can only be reached via lockable access
- Externally mounted emergency stop button
- Designed for spreader-bar lifting to ensure safety
- Control panel viewing window
- Stub-up area is rodent proof

OPTIONS

- Caterpillar Yellow or white paint
- Integral dual wall fuel tank base for total fluid containment (fuel, oil and coolant)


HIGH AMBIENT ENCLOSURE OPERATING CHARACTERISTICS

60 Hz CAHA Enclosure (Low BSFC)			Ambient Capability*		Airflow Rate		Sound Pressure Levels dBA @ Full Load			Exhaust Back Pressure	
ekW	kVA	PP/SB	°C	°F	m ³ /s	cfm	1m	7m	15m	In/H ₂ O	kPa
400	500.0	SB	51	124	7.9	16739	89.5	77.0	71.0	7.6	1.9
350	437.5	PP	52	126	7.9	16739	88.5	76.2	70.2	6.4	1.6
350	437.5	SB	58	136	7.9	16739	88.5	76.2	70.2	6.4	1.6
320	400.0	PP	56	133	7.9	16739	87.9	75.7	69.7	5.9	1.5

*Ambient measured with Caterpillar Extended Life Coolant

50 Hz CAHA Enclosure (Low BSFC)			Ambient Capability*		Airflow Rate		Sound Pressure Levels dBA @ Full Load			Exhaust Back Pressure	
ekW	kVA	PP/SB	°C	°F	m ³ /s	cfm	1m	7m	15m	In/H ₂ O	kPa
360	450	SB	49	120	5.6	11866	88.1	76.6	70.6	6.0	1.5
320	400	PP	49	120	5.6	11866	87.2	75.5	69.5	5.0	1.2
320	400	SB	54	129	5.6	11866	87.2	75.5	69.5	5.0	1.2
280	350	PP	54	129	5.6	11866	86.2	74.4	68.4	4.4	1.1

*Ambient measured with Caterpillar Extended Life Coolant



Approximate weight of enclosure package: 4780 kg (10,538 lb). Exact weight is dependent on options. Enclosure weight includes: sound attenuated enclosure, exhaust system, base and generator set. Generator set enclosure also available in white. (Caterpillar yellow is standard colour)

Information contained in this publication may be considered confidential.
Discretion is recommended when distributing.

Materials and specifications are subject to change without notice.
CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

www.Cat-ElectricPower.com

© 2013 Caterpillar
All Rights Reserved.
Printed in U.S.A.