

PDL-300KW Dummy Load Bank

GENERAL FEATURES:

GENELITE LOAD BANK SERIES

Designed for durability and convenience with its heavy duty enclosure, cable termination block, lifting eyes and optional heavy duty caster wheels.

Units utilise low heat emitting resistive elements to minimise heat conduction. Metal sheathed elements with cooling fins made from high grade nickel resistance wire in U-type form.

Built in heavy duty cooling system with industrial type blower fan. Fans can be powered internally by the dummy load itself or by external power supply.

Incremental load testing feature using 7 switches and variable load testing feature using rheostat for exact power setting.

Digital display meters for voltage, amperes, frequency and power factor.



SPECIFICATIONS

SPECIFICATIONS	
MODEL	PDL - 300KW
Rate of Load	0 ~ 300KW
Type of load	Resistive
Duty	Continuous
Enclosure	Outdoor
Phase	3 Phase
Rated Voltage	415V
Rated Frequency	50Hz
Load Step	18 / 18 / 27 / 27 / 54 / 54 / 108 kW
Dimensions (mm)	1100(L) x 1270(W) x 1470(H)
Dry Weight	880Kg

POWER YOU CAN RELY ON

HEAD OFFICE: 24 Perrin Place, Salisbury QLD 4107 • PO Box 115 Archerfield QLD 4108 • ABN 40 095 032 385

BRISBANE

Phone: (07) 3277 8626 • Fax: (07) 3277 8627

PERTH

Phone: (08) 9300 6168 • Fax: (08) 9300 6471

PORT HEDLAND

Phone: 1300 305 912

Email: info@genelite.com.au • www.genelite.com.au