

GH16000E-FBT/3 16kVA HONDA

**16kVA
HONDA**
GH16000E-FBT/3



ENGINE

MANUFACTURER	Honda
ENGINE MODEL	GX690E
TYPE & CYLINDER	O.H.V.
STARTING	Electric Start
RUN TIME	11hrs @ 60% load
FUEL	Unleaded Petrol
CUBIC CAPACITY	688 cm ³
HP 3000 RPM CONT	14.1HP
OIL CAPACITY	1.9L

TECHNICAL

MODEL	GH16000E-FBT/3
TYPE	Portable
FREQUENCY	50Hz
PHASE/VOLTAGE	3/415

SPEED	POWER		NOISE LEVEL	FUEL CAPACITY	CONTINUOUS OUTPUT
	Max Power		dBA @7m see *1		
	kW	kVA	dBA		
3000RPM	13	16	74	50L	16kVA

ADDITIONAL INFO

OUTLETS	1 x 32 amp 415V 2 x 15 amp 240V switched with thermal overload
FRAME	Skid base with roll frame

DIMENSIONS

LENGTH	105cm
WIDTH	77cm
HEIGHT	56cm
WEIGHT	155kg

ALTERNATOR

ALTERNATOR BRAND	Mecc Alte
TYPE	Brushless
HARMONIC DISTORTION	Less than 5%
INSULATION CLASS	Class H

OPTIONS

- Weather protected IP66 outlets
- 4 wheel kit