



HINO

GH72

Model GH72
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 79kVA / 63kW
Prime Output 72kVA / 57kW

Length 2.20m
Width 1.10m
Height 2.0m
Weight 1200kg

Engine

Manufacturer Hino Diesel
Engine Model W04DT1
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged
Fuel Consumption
15.4L @ 100%, 12.0L @ 75%, 4.5L @ 50% Load
Coolant Capacity 10 L
Governor Mechanical
Cubic Capacity 4.0 L
Oil Capacity 14 L

Options

Outlets Single or 3 Phase Options
PMG EBS option

Controls

Key Start
Circuit Breaker Four Pole
Emergency Stop Included

Alternator

Alternator Brand / Model Stamford / UCi224F
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Note: All details are subject to change.

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
6 Flindell Street, O'Connor WA 6163

CALL US
1300 305 912