



TECHNICAL OVERVIEW

MODEL	GMS2000
LIGHTS	4 x 500 W LED
LUMINOUS FLUX	202,600 LMS
MAST	TELESCOPIC MAST WITH 359° MANUAL ROTATION
HEIGHT	9 M
LIFTING SYSTEM	HYDRAULIC
TILTING ANGLE	90°
WIND RATING SPEED	102 KM / H
MAX TOWING SPEED	80 KM / H

ENGINE

MANUFACTURER	KUBOTA
ENGINE MODEL	Z482-E4B-ACP-1
CYLINDER/ CAPACITY	2 CYL / 0.479 LTR
INDUCTION	NATURALLY ASPIRATED
FUEL CONSUMPTION	0.76 L/HR @ 75% LOAD
GOVERNOR	ELECTRONIC
OIL CAPACITY	2.5 LTR
COOLANT CAPACITY	10 LTR

ALTERNATOR

BRAND AND MODEL	POWERLINK PMG-DC
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
VOLTAGE	48 V DC

FEATURES

KUBOTA POWERED DIESEL LIGHTING TOWER
SILENCED CANOPY – 53 dB(A) @ 7M
90 LITRE FUEL TANK / 132 HRS RUN TIME @ 100% LOAD
HYDRAULIC MAST
CANOPY – POWDER COAT
REMOTE MONITORING CONTROL SYSTEM
DC 48 V

CONTROLS

MODEL	C-805
OPERATION	MANUAL, AUTOMATIC AND REMOTE

TRAILER

MOBILE SINGLE AXLE TRAILER
AUSTRALIAN STANDARD
50 MM BALL 2000 KG TOWING HITCH
ELECTRIC BRAKING SYSTEM
STABILISATION LEG: 4 x LEGS MANUAL
SPRING TYPE SUSPENSION SYSTEM
TRANSPORTATION: TRUCK, CRANE, FORKLIFT
TYRE AND RIM: 175 R13 LT

OPTIONS

MINE SPEC
ALTERNATIVE COUPLING OPTIONS

DIMENSIONS

LENGTH / WIDTH / HEIGHT (RETRACTED)	240 CM / 145 CM / 228 CM
WEIGHT (DRY)	890 KG

