



Genette



PLGCT28S

Model PLGCT28S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 28kVA / 22 kW
Prime Output 25kVA / 20 kW
Noise Level @ 7m 71 dB(A)
Fuel Capacity 310 Litres

Length 2.40m
Width 1.000m
Height 1.580m
Weight 1250 kg

Engine

Manufacturer Cummins Diesel
Engine Model 4B3.9-G1
Type & Cylinder 4 Stroke – 6 L
Induction Naturally Aspirated
Fuel Consumption
6.7L @ 100%, 5.2L @ 75%, 4.0L @ 50% Load
Coolant Capacity 8 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 11 L

Canopy - Galvanised Powder Coat

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Lockable doors with control panel viewing window
Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External

Controls

Controller DeepSea 4520 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Included
Battery Charger 24vDC 5amp

Alternator

Alternator Brand / Model Leroy Somer TAL-A40-6
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Outlets Single or 3 phase options
PMG EBS option
Mine spec
Synchronising controls
Jacket water heater
Auto transfer switch options

East Coast Head Office Ph. 1300 305 912 West Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627 Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
24 Perrin Place, Salisbury QLD 4107 6 Flindell Street, O'Connor WA 6163

CALL US
1300 305 912