



PORTABLE

SCREW COMPRESSOR

CF400BC-7

SERIES



AIR PRESSURE: 7 Bar / 101.5 PSI
FAD: 400 CFM / 11.3 m³/min

Main Improvements:

Availability for wide application

Genelite model is line up to suit a wide range of applications such as pneumatic tools drilling and blasting.

Easy Starting in Cold Weather

This compressor is superior in cold weather starting.

Meters with Luminous Lights

Meters on operation panel are equipped with luminous light.

Reliable Warning Signal

Warning signals have luminiscent diode and so become more reliable.



Double Element Air Cleaner

Double element air cleaner prevents dust from entering when replacing element.

Easy Cleaning of Cooling System

This compressor is so designed that the interiors of radiator and oil cooler and also fuel tank can be easily and quickly clean





COMPRESSOR

Type	Rotary twin screw, single stage, oil-cooled
Free air delivery	11.3 m ³ /min(400 cfm)
Working pressure	7 bar (101.5 psi)
Unloader	Suction port closing in connection with stepless speed regulator
Lubrication system	Forced lubrication by compression pressure
Driving system	Direct coupling with rubber
Oil cooling	Air-cooled
Air cleaner	Dry paper filter type

OIL SEPARATOR-RECEIVER TANK

Type	Vertical, cylindrical, full-welded
Shell dia	350 mm
Shell length	940 mm
Capacity	75 L
Max. working pressure	1.58MPa
Hydraulic test pressure	2.37MPa
Air outlet valve	3pcs x 3 /4" + 1pc x 2"
Recommend Oil type	#46

DIESEL ENGINE

Model	CUMMINS 4BTA3.9-C125
Type	Water-cooled, 4-cycle, Direct-Injection, Turbo-Charged type
No. Of cylinders	4
Bore x stroke	102 mm x 120 mm
Total displacement	3.9 liters
Compression ratio	17.3 : 1
Rated output	93 kW(125PS) 2,200rpm
Max.torque	475 N.m/approx.1,500rpm
Governor	Mechanical
Battery	60AH X 2 pcs, 580CCA
Air cleaner	Two-stage dry type

INSTRUMENTS & GAUGES

EMERGENCY STOP DEVICES

Oil pressure switch
Engine coolant temperature switch
Discharge air temperature switch
Compressor oil temperature switch
Engine speed down switch

GAUGES

Air Pressure gauge	Tachometer
Fuel level gauge	Engine oil pressure
Stop button	Engine coolant temp
Starter switch	Discharge air temp
Starting Loader	Discharge air pressure
	Hourmeter

LIQUID CAPACITY

Fuel tank capacity	160 liters
Engine oil capacity	9 liters
Coolant capacity	30 liters
Compressor oil capacity	60 liters

DIMENSIONS & WEIGHT

L x W x H	2657 x 1355 x 1466 mm
Weight	1850 Kg



GENELITE PTY LTD

24 Perrin Place, Salisbury, QLD 4107
 6 Flindell Street, O'Connor, WA 6163
 PH: 1300 305 912
 E-mail:sales@genelite.com.au
 http: www.genelite.com.au



SAFETY

- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.

