

INDUSTRIAL DIESEL UTILITY AIR **COMPRESSOR**



Technical

Model **CPS T250**

Type Box-Type Skid-Mounted

Air Delivery Utility 250CFM **Normal Effective**

7bar(g) @ 100psi(g) **Working Pressure**

Engine

Manufacturer Kubota V 2403 T Type Starting Electric Start **Fuel** Diesel **Full Load RPM** 3000 RPM **Tank Capacity** 100 L Output Rating (kW/m) 47.9

Compressor

Single Stage Oil Injected Rotary Screw Air **Type**

Compressor

Lube Oil Capacity 11 L

Controls

Control Panel Key Start with Engine Protection **Blow Off Valve** Automatic on Shutdown

Box Unit Dimensions & Weight

Length 2050mm Width 1200mm 1230mm Heiaht Weight 1200kg

Canopy

Canopy Galvanised Steel Canopy

Noise Level 70dB(A) @ 7m Spillage free frame Frame

Standard Features

Fully Silenced Canopy

Integrated lifting slots and top hook as standard

Aftercooler Fitted as Factory Standard Mounting Suitable for truck or trailer mounting

Fuel Autonomy Enough to run a full shift

Weight Under 1250kg

Footprint At least 10% more compact than other models Maintenance Easy to service & long service intervals

Other Features

Mounting Suitable for truck mounting

Quality air options, water separator and multiple **Options**

points of customisation available



Authorized Distributor