



Geneite



PLGCT130S

Model PLGCT130S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 143kVA / 116 kW
Prime Output 130kVA / 104 kW
Noise Level 78 dB(A)
Fuel Capacity 500 Litres

Length 3.00m
Width 1.106m
Height 1.786m
Weight 1850kg

Engine

Manufacturer Cummins Diesel
Engine Model 6BTAA5.9-P160
Type & Cylinder 4 Stroke – V16
Induction Turbocharged Air to Air After Cooled
Fuel Consumption
30 L @ 100%, 23L @ 75%, 16L @ 50% Load
Coolant Capacity 10.4 L
Governor Electronic
Cubic Capacity 5.9 L
Oil Capacity 16.4 L

Canopy - Galvanised Powder Coat

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Lockable doors with control panel viewing window
Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External

Controls

Controller DeepSea 4520 Auto
Circuit Breaker 4 Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Leroy Somer
TAL-A44-H 128kVA
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Outlets Single or 3 Phase options
PMG option
Mine spec
Synchronising controls
Jacket water heater
Auto transfer switch options

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
6 Flindell Street, O'Connor WA 6163

CALL US
1300 305 912