



TECHNICAL OVERVIEW

MODEL	DHY14KSE-3
PRIME POWER	13 kVA / 10.4 kW
STANDBY POWER	14 kVA / 11.2 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
DUTY	CRITICAL STANDBY / LIMITED PRIME
FREQUENCY	50Hz
PHASE/VOLTAGE	THREE PHASE / 415V
FUEL CAPACITY	80 LTR

ENGINE

ENGINE MODEL	H4DW81-23D
CYLINDER/ CAPACITY	4 CYL / 2.27 LTR
INDUCTION	NATURALLY ASPIRATED
FUEL CONSUMPTION	4.98 L/HR @ 100% LOAD 3.8 L/HR @ 75% LOAD 2.7 L/HR @ 50% LOAD
GOVERNOR	ELECTRONIC
OIL CAPACITY	7.8 LTR
COOLANT CAPACITY	15.5 LTR

FEATURES

SILENCED CANOPY – 67dB(A) @ 7M
HEAVY DUTY SKID BASE WITH FORK POCKETS
BUNDED FUEL TANK – 21 HOUR RUN TIME @ 75% LOAD
CANOPY – GALVANISED POWDER COAT
BATTERY CHARGER AND ISOLATOR
OUTLETS – 1 x 32 AMP 415V, 2 x 15 AMP 240V

CONTROLS

BRAND AND MODEL	DEEPSEA 6120
CIRCUIT BREAKER	FOUR POLE

ALTERNATOR

BRAND AND MODEL	HYUNDAI HK164C
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

OPTIONS

MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

DIMENSIONS

LENGTH / WIDTH / HEIGHT	203.8 CM / 85 CM / 112.5 CM
WEIGHT (DRY)	900 KG

PRIME POWER (PRP): Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

STANDBY POWER RATING (ESP): Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.