



### TECHNICAL OVERVIEW

MODEL	GC320S
PRIME POWER	320 kVA / 256 kW
STANDBY POWER	352 kVA / 282 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
TYPE	HEAVY DUTY
FREQUENCY	50Hz
PHASE/VOLTAGE	THREE PHASE / 415V
FUEL CAPACITY	1500 LTR

### ENGINE

MANUFACTURER	CUMMINS
ENGINE MODEL	6LTAA9.5-G1
CYLINDER/ CAPACITY	6 CYL / 9.5 LTR
INDUCTION	TURBO AFTER COOLED
FUEL CONSUMPTION	70 L/HR @ 100% LOAD 52 L/HR @ 75% LOAD 35 L/HR @ 50% LOAD
GOVERNOR	ELECTRONIC
OIL CAPACITY	32.4 LTR
COOLANT CAPACITY	54 LTR

### FEATURES

SILENCED CANOPY – 75.7 dB(A) @ 7M
HEAVY DUTY SKID BASE WITH FORK POCKETS
BUNDED FUEL TANK – 29 HOUR RUN TIME @ 75% LOAD
CANOPY – GALVANISED POWDER COAT
BATTERY CHARGER AND ISOLATOR

### CONTROLS

BRAND AND MODEL	DEEPSEA 7420 MKII
CIRCUIT BREAKER	FOUR POLE

### ALTERNATOR

BRAND AND MODEL	STAMFORD S4L1D-E4
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

### OPTIONS

OUTLETS
MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

### DIMENSIONS

LENGTH / WIDTH / HEIGHT	424.2 CM / 146.3 CM / 248.2 CM
WEIGHT (DRY)	4140 KG

**PRIME POWER (PRP):** Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

**STANDBY POWER RATING (ESP):** Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.

