



TECHNICAL OVERVIEW

MODEL	GC750S
PRIME POWER	750 kVA / 600 kW
STANDBY POWER	825 kVA / 660 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
TYPE	HEAVY DUTY
FREQUENCY	50Hz
PHASE/VOLTAGE	THREE PHASE / 415V
FUEL CAPACITY	1450 LTR

ENGINE

MANUFACTURER	CUMMINS
ENGINE MODEL	KTA38G2B
CYLINDER/ CAPACITY	12 CYL / 37.5 LTR
INDUCTION	TURBO AFTER COOLED
FUEL CONSUMPTION	160 L/HR @ 100% LOAD 120 L/HR @ 75% LOAD 83 L/HR @ 50% LOAD
GOVERNOR	ELECTRONIC
OIL CAPACITY	135 LTR
COOLANT CAPACITY	194 LTR

FEATURES

SILENCED CONTAINER – 78.8 dB(A) @ 7M
ISO CONTAINER 20FT
BUNDED FUEL TANK – 12 HOUR RUN TIME @ 75% LOAD
BATTERY CHARGER AND ISOLATOR

CONTROLS

BRAND AND MODEL	DEEPSEA 7420 MKII
CIRCUIT BREAKER	FOUR POLE

ALTERNATOR

BRAND AND MODEL	LEROY SOMER LSA49.3M8
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

OPTIONS

OUTLETS
MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

DIMENSIONS

LENGTH / WIDTH / HEIGHT	605.8 CM / 243.8 CM / 259.1 CM
WEIGHT (DRY)	11776 KG

PRIME POWER (PRP): Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

STANDBY POWER RATING (ESP): Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.



LEROY-SOMER™

