



### TECHNICAL OVERVIEW

MODEL	GC80S
PRIME POWER	80 kVA / 64 kW
STANDBY POWER	88 kVA / 70 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
TYPE	HEAVY DUTY
FREQUENCY	50Hz
PHASE/VOLTAGE	THREE PHASE / 415V
FUEL CAPACITY	450 LTR

### ENGINE

MANUFACTURER	CUMMINS
ENGINE MODEL	4BTA3.9-G11
CYLINDER/ CAPACITY	4 CYL / 3.9 LTR
INDUCTION	TURBO AFTER COOLED
FUEL CONSUMPTION	17.6 L/HR @ 100% LOAD 13.2 L/HR @ 75% LOAD 9.1 L/HR @ 50% LOAD
GOVERNOR	MECHANICAL
OIL CAPACITY	10.9 LTR
COOLANT CAPACITY	29 LTR

### FEATURES

SILENCED CANOPY – 68.2 dB(A) @ 7M
HEAVY DUTY SKID BASE WITH FORK POCKETS
BUNDED FUEL TANK – 34 HOUR RUN TIME @ 75% LOAD
CANOPY – GALVANISED POWDER COAT
BATTERY CHARGER AND ISOLATOR

### CONTROLS

BRAND AND MODEL	DEEPSEA 7420 MKII
CIRCUIT BREAKER	FOUR POLE

### ALTERNATOR

BRAND AND MODEL	STAMFORD UC1224G
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

### OPTIONS

OUTLETS
MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

### DIMENSIONS

LENGTH / WIDTH / HEIGHT	268.8 CM / 105 CM / 178.9 CM
WEIGHT (DRY)	1650 KG

**PRIME POWER (PRP):** Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

**STANDBY POWER RATING (ESP):** Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.

