



MODEL OVERVIEW

SPEED	3000RPM
POWER	14.4kW / 18kVA
FUEL TYPE	PETROL
FUEL CAPACITY	25L
CONTINUOUS OUTPUT	18kVA

ADDITIONAL INFO

OUTLETS	1 x 32AMP IP66 WITH RCD & C/B 2 x 15 AMP IP66 WITH RCD & C/B
FRAME	EXTRA LARGE ROLL FRAME
NOISE RATING	78 dBA @ 7M

TECHNICAL

MODEL	GHP18000E-LRT-H
TYPE	PORTABLE
FREQUENCY	50Hz
PHASE/VOLTAGE	1/240

Hyundai Powered Heavy Duty Industrial Generators

Featuring a durable open-frame design and genuine Hyundai Engine, these generators are designed to provide maximum power output, making them perfect for heavy-duty applications. They deliver consistent and stable power to keep your tools, equipment, and appliances running smoothly. With unmatched durability and performance, these generators are built to handle even the toughest jobs.

FEATURES

HYUNDAI PETROL ENGINE
HEAVY DUTY ROLL FRAME
ELECTRIC START
3 YEAR LIMITED ENGINE WARRANTY

ENGINE

MANUFACTURER	HYUNDAI
ENGINE MODEL	H740E
TYPE & CYLINDER	O.H.V. SINGLE CYLINDER
STARTING	ELECTRIC START
RUN TIME	7 HR @ 60% LOAD
CUBIC CAPACITY	740 CM ³
HP 3000 RPM CONT	23 HP
OIL CAPACITY	1.9 L

ALTERNATOR

TYPE	AC SYNCHRONOUS BRUSHLESS
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

DIMENSIONS

LENGTH / WIDTH / HEIGHT	87 CM / 60 CM / 77 CM
WEIGHT (DRY)	145 KG

OPTIONS

WEATHER PROTECTED IP66 OUTLETS
RCD/ELCB PROTECTION
2 OR 4 WHEEL KIT
FUEL TANK BASE WITH ROLL OVER FRAME

The warranty does not cover damage caused by misuse, neglect, accident, improper installation, unauthorised repairs or modifications, normal wear and tear, or use of non-approved fuels or oils. Consumable parts such as filters, fuses, and cosmetic wear are not covered.

The generator must be serviced at regular intervals as specified in the user manual. Proof of purchase and service records may be required. As the Australian distributor, Genelite reserves the right to repair or replace defective parts at its discretion.