



TECHNICAL OVERVIEW

MODEL	GK10S
PRIME POWER	10 kVA / 8 kW
STANDBY POWER	11 kVA / 8.8 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
TYPE	HEAVY DUTY
FREQUENCY	50Hz
PHASE/VOLTAGE	THREE PHASE / 415V
FUEL CAPACITY	130 LTR

ENGINE

MANUFACTURER	KUBOTA
ENGINE MODEL	D1105-BG
CYLINDER/ CAPACITY	3 CYL / 1.123 LTR
INDUCTION	NATURALLY ASPIRATED
FUEL CONSUMPTION	3.5 L/HR @ 100% LOAD 2.9 L/HR @ 75% LOAD 1.8 L/HR @ 50% LOAD
GOVERNOR	MECHANICAL
OIL CAPACITY	5.1 LTR
COOLANT CAPACITY	10 LTR

FEATURES

SILENCED CANOPY – 66.6 dB(A) @ 7M
HEAVY DUTY SKID BASE WITH FORK POCKETS
BUNDED FUEL TANK – 44 HOUR RUN TIME @ 75% LOAD
CANOPY – GALVANISED POWDER COAT
BATTERY CHARGER AND ISOLATOR
OUTLETS – 2 x 15 AMP 240V, 1 x 20 AMP 415V

CONTROLS

BRAND AND MODEL	DEESEA 4520 MKII
CIRCUIT BREAKER	FOUR POLE

ALTERNATOR

BRAND AND MODEL	STAMFORD SOL1-H1
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

OPTIONS

MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

DIMENSIONS

LENGTH / WIDTH / HEIGHT	194.2 CM / 83 CM / 127.8 CM
WEIGHT (DRY)	659 KG

PRIME POWER (PRP): Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

STANDBY POWER RATING (ESP): Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.

