



TECHNICAL OVERVIEW

MODEL	GK20S-1
PRIME POWER	20 kVA / 16 kW
STANDBY POWER	22 kVA / 18 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
TYPE	HEAVY DUTY
FREQUENCY	50Hz
PHASE/VOLTAGE	SINGLE PHASE / 240V
FUEL CAPACITY	100 LTR

ENGINE

MANUFACTURER	KUBOTA
ENGINE MODEL	V2203-BG
CYLINDER/ CAPACITY	4 CYL / 1,647 LTR
INDUCTION	NATURALLY ASPIRATED
FUEL CONSUMPTION	5.5 L/HR @ 100% LOAD 4.1 L/HR @ 75% LOAD 2.8 L/HR @ 50% LOAD
GOVERNOR	MECHANICAL
OIL CAPACITY	7.6 LTR
COOLANT CAPACITY	41 LTR

FEATURES

SILENCED CANOPY – 67 dB(A) @ 7M
HEAVY DUTY SKID BASE WITH FORK POCKETS
BUNDED FUEL TANK – 24 HOUR RUN TIME @ 75% LOAD
CANOPY – GALVANISED POWDER COAT
BATTERY CHARGER AND ISOLATOR
OUTLET – 4 x 15 AMP 240V

CONTROLS

BRAND AND MODEL	DEEPSEA 4520 MKII
CIRCUIT BREAKER	FOUR POLE

ALTERNATOR

BRAND AND MODEL	STAMFORD PI144
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

OPTIONS

MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

DIMENSIONS

LENGTH / WIDTH / HEIGHT	213.2 CM / 92.7 CM / 130.4 CM
WEIGHT (DRY)	878 KG

PRIME POWER (PRP): Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

STANDBY POWER RATING (ESP): Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.

