



GENELITE LOAD BANK SERIES

Designed to help protect your generator investment, this load bank can be permanently installed indoors or outdoors. The smart control panel automatically keeps generators operating at an optimum operating load, helping to prevent issues like wet stacking and cylinder glazing.

Engineered for Australia's harsh conditions, this load bank boasts a rugged design, capable of operating in ambient temperatures up to 50°C.

Ideal for generator applications for maintaining minimum loads, as well as on site testing. It is a great solution for demanding sectors such as mining camps, data centres, commercial buildings, telecommunications, essential services, defence and power stations.

| SPECIFICATIONS | |
|-----------------|---------------|
| MODEL | GLB-550 kW |
| OPERATION | AUTOMATIC |
| RATE OF LOAD | 0 – 550 kW |
| TYPE OF LOAD | RESISTIVE |
| DUTY | CONTINUOUS |
| RATED VOLTAGE | 415V |
| RATED FREQUENCY | 50 Hz / 60 Hz |
| POWER FACTOR | 1 |

| ADDITIONAL INFO | |
|---------------------|--|
| ENCLOSURE | OUTDOOR |
| LOAD STEP | 1 / 2 / 2 / 5 / 10 / 10 / 20 / 50 / 100 / 100 / 125 / 125 kW |
| AIRFLOW | 8.5 M ³ /S |
| TERMINALS PER PHASE | 2 x M12 |

| FEATURES | |
|----------------------------|--|
| GALVANISED STEEL CANOPY | |
| SOUND LEVEL – 78 dBA | |
| GALVANISED SKID BASE | |
| TOP LIFT WITH FORK POCKETS | |
| STAINLESS STEEL ELEMENTS | |
| 7" HMI INSTRUMENT DISPLAY | |

| DIMENSIONS | |
|--------------|---------|
| LENGTH | 241 CM |
| WIDTH | 176 CM |
| HEIGHT | 193 CM |
| WEIGHT (DRY) | 1290 KG |

| OPTIONS | |
|------------------------|--|
| MOBILE TRAILER OPTIONS | |
| CABLE SETS | |