



MODEL OVERVIEW	
SPEED	3000RPM
POWER	2kW / 2.2kVA
FUEL TYPE	DIESEL
FUEL CAPACITY	2.5L
CONTINUOUS OUTPUT	2.2kVA

ADDITIONAL INFO	
OUTLETS	2 x 10AMP 240V GPO SWITCHED WITH THERMAL OVERLOAD
FRAME	LARGE ROLL FRAME
NOISE RATING	80 dBA @ 7M

TECHNICAL	
MODEL	GYD2000E
TYPE	PORTABLE
FREQUENCY	50Hz
PHASE/VOLTAGE	1/240

Yanmar Powered Heavy Duty Industrial Generators

This range from Genelite proudly features a genuine Yanmar engine, that delivers reliable, high-performance power for homes, businesses and job sites.

Featuring a durable open frame design, these generators are designed to provide maximum power output, making them perfect for heavy-duty applications. They deliver consistent and stable power to keep your tools, equipment, and appliances running smoothly. With unmatched durability and performance, these generators are built to handle even the toughest jobs.

Materials and specifications are subject to change. Specification sheets are current as of 30/6/2025.

FEATURES	
YANMAR DIESEL ENGINE	
HEAVY DUTY ROLL FRAME	
ELECTRIC START	
2 YEAR LIMITED ENGINE WARRANTY	

ENGINE	
MANUFACTURER	YANMAR
ENGINE MODEL	L48AE-DEG
TYPE & CYLINDER	O.H.V. SINGLE CYLINDER
STARTING	ELECTRIC START
RUN TIME	4.1 HR @ 75% LOAD
CUBIC CAPACITY	296 CM ³
HP 3000 RPM CONT	3.8 HP
OIL CAPACITY	1.1 L

ALTERNATOR	
TYPE	AC SYNCHRONOUS BRUSHLESS
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

DIMENSIONS	
LENGTH	77 CM
WIDTH	49 CM
HEIGHT	57 CM
WEIGHT (DRY)	54 KG

OPTIONS	
HIRE SPEC: 2 x IP56 RATED OUTLETS, CIRCUIT BREAK and RCD PROTECTION	
MINE SPEC UPGRADE	
2 OR 4 WHEEL KIT	
LONG RANGE TANK	

The warranty does not cover damage caused by misuse, neglect, accident, improper installation, unauthorised repairs or modifications, normal wear and tear, or use of non-approved fuels or oils. Consumable parts such as filters, fuses, and cosmetic wear are not covered.

The generator must be serviced at regular intervals as specified in the user manual. Proof of purchase and service records may be required. As the Australian distributor, Genelite reserves the right to repair or replace defective parts at its discretion.