



TECHNICAL OVERVIEW

MODEL	LG30K-1
PRIME POWER	30 kVA / 24 kW
STANDBY POWER	33 kVA / 26.4 kW
FUEL TYPE	DIESEL
SPEED	1500 RPM
TYPE	HEAVY DUTY
FREQUENCY	50Hz
PHASE/VOLTAGE	SINGLE PHASE / 240V
FUEL CAPACITY	185 LTR

ENGINE

MANUFACTURER	KUBOTA
ENGINE MODEL	V3303
CYLINDER/ CAPACITY	4 CYL / 3.318 LTR
INDUCTION	NATURALLY ASPIRATED
FUEL CONSUMPTION	7.7 L/HR @ 100% LOAD 5.9 L/HR @ 75% LOAD 4.2 L/HR @ 50% LOAD
GOVERNOR	MECHANICAL
OIL CAPACITY	13.2 LTR
COOLANT CAPACITY	15 LTR

FEATURES

SILENCED CANOPY – 67 dB(A) @ 7M
HEAVY DUTY SKID BASE WITH FORK POCKETS
BUNDED FUEL TANK – 31 HOUR RUN TIME @ 75% LOAD
CANOPY – GALVANISED POWDER COAT
BATTERY CHARGER AND ISOLATOR
OUTLETS – 3 x 15 AMP 240V, 1 x 32 AMP 240V

CONTROLS

BRAND AND MODEL	DEEPSEA 6120
CIRCUIT BREAKER	TWO POLE

ALTERNATOR

BRAND AND MODEL	STAMFORD S1L2-N1
TYPE	BRUSHLESS / AVR
HARMONIC DISTORTION	LESS THAN 5%
INSULATION CLASS	CLASS H

OPTIONS

ADDITIONAL OUTLETS
MINE SPEC
JACKET WATER HEATER
EXTERNAL FUEL CONNECTION
AUTO TRANSFER SWITCHES (ATS)

DIMENSIONS

LENGTH / WIDTH / HEIGHT	228.8 CM / 95 CM / 140 CM
WEIGHT (DRY)	977 KG

PRIME POWER (PRP): Continuous operation at variable load unlimited hours per year, with an average load factor of 75%. 10% overload capability is 1 hour in a 12 hour period of operation.

STANDBY POWER RATING (ESP): Emergency power supply with an average load factor of 85%. No overload capability. Limited to 400 hours per year.